

bind configuration

```
$TTL 1W
@IN$SOA ns1.example.com. root (
    2019070700; serial
    3H; refresh (3 hours)
    30M; retry (30 minutes)
    2W; expiry (2 weeks)
    1W ) minimum (1 week)
IN NS ns1.example.com.
IN MX 10 smtp.example.com.
;
;
ns1.example.com. IN A 192.168.1.5
smtp.example.com. IN A 192.168.1.5
;
helper.example.com. IN A 192.168.1.5
helper.ocp4.example.com. IN A 192.168.1.5
;
api.ocp4.example.com. IN A 192.168.1.5
api-int.ocp4.example.com. IN A 192.168.1.5
;
*.apps.ocp4.example.com. IN A 192.168.1.5
;
bootstrap.ocp4.example.com. IN A 192.168.1.96
;
master0.ocp4.example.com. IN A 192.168.1.97
master1.ocp4.example.com. IN A 192.168.1.98
master2.ocp4.example.com. IN A 192.168.1.99
;
worker0.ocp4.example.com. IN A 192.168.1.11
worker1.ocp4.example.com. IN A 192.168.1.7
;
;EOF
```

Revision #1

Created 13 January 2023 04:28:34 by Admin

Updated 13 January 2023 04:35:09 by Admin