

Ubuntu 🐧

📄 📄 📄

```
sudo apt install bind9 bind9utils bind9-doc
```

IPv4 📄 📄 📄 📄

```
sudo vi /etc/default/named
```

```
OPTIONS="-u bind -4"
```

/etc/bind/named.conf.local

```
zone "spelix.com" IN {
    type master;
    file "/etc/bind/zones/db.spelix.com";
    allow-update { none; };
};
```

/etc/bind/zones/db.spelix.com

- zones 📄 📄 📄 📄 📄.
- zone 📄 📄 📄 (row, 📄) 📄 📄 📄 📄.

```
$TTL 1D
spelix.com. IN SOA ns1.spelix.com. krauss.spelix.com. (
    1          ; serial
    10800      ; refresh after 3 hours
    3600       ; retry after 1 hour
    604800     ; expire after 1 week
    86400      ; minimum TTL of 1 day
)

spelix.com. IN NS ns1.spelix.com.
```

ns1.spelix.com. IN A 115.71.1.39

m1.packstack.spelix.com. IN A 115.71.1.40

; web server that is places out side of this local network

www.spelix.com. IN A 34.149.87.45

ntp.spelix.com. IN CNAME ns1.spelix.com.

Revision #2

Created 13 January 2023 04:46:58 by Admin

Updated 13 January 2023 04:49:24 by Admin